

Alpha Series Handbook

| Technical Specifications | |
|----------------------------|---|
| GTLS RATING | T100 |
| CASE MATERIAL | 316 stainless steel |
| CASE FINISH | Black PVD or brushed stainless steel |
| STRAP TYPE | Polymer or stainless steel bracelet |
| CRYSTAL | Sapphire with triple anti-reflective coating |
| MOVEMENT TYPE | Quartz |
| MOVEMENT | Swiss made Ronda 715Li |
| CROWN TYPE | Screw down |
| DIAL DIAMETER | 31mm |
| CASE DIAMETER | 42mm |
| CASE DEPTH | 14.8mm |
| LUG WIDTH | 22mm |
| FIXING TYPE | 2 x 22mm spring bars |
| WEIGHT | 116g Fitted on polymer strap 182g Fitted on steel bracelet |
| WATER RESISTANCE | 300m |
| BATTERY LIFE | 10 Years |
| LUG TO LUG (TOP TO BOTTOM) | 50mm |

Setting the time and date

Pos. I Position of rest (watch running)

Pos. II Quick-change correction for date

Blocking time for the quick-change day correction is from approx. 9.30 pm and midnight.

- Unscrew the crown by turning anti-clockwise (watch still running).
- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.
- Gently push and screw the crown clockwise to secure it into the case.

Pos. III Setting the time

- Unscrew the crown by turning anti-clockwise (watch still running).
- Pull the crown out to position III (watch stopped).

- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.
- Gently push and screw the crown clockwise to secure it into the case.



Strap fitting/options

The Alpha models can be fitted with a polymer strap, one-piece 22mm webbing or a stainless-steel bracelet.

With a 22mm lug width and 22mm spring bar fixing, straps are easily interchangeable using a forked spring bar tool. Many 22mm aftermarket straps are also compatible*

The Alpha straps exclusively available through nitewatches.com can be found [here](#).

The stainless-steel bracelet can be adjusted in length by adding or removing links and by also using the 3-micro adjustment on the buckle part of the strap.

**Nite Watches accept no responsibility with the sizing and fitting of any aftermarket straps.*

If you have any questions about the Alpha series then please email us on theteam@nitewatches.com.