

Hawk Series Handbook

Technical Specifications	
TRITIUM RATING	T25 or T100
CASE FINISH	Black polycarbonate
STRAP TYPE	Polymer or stainless steel bracelet
CRYSTAL	Sapphire with triple anti-reflective coating
MOVEMENT TYPE	Quartz
MOVEMENT	Swiss made Ronda 715Li
CROWN TYPE	Push
DIAL DIAMETER	33mm
CASE DIAMETER	51mm
CASE DEPTH	14.6mm
LUG WIDTH	24mm
FIXING TYPE	2 x 24mm spring bars
WEIGHT	70g Fitted on polymer strap 162g Fitted on steel bracelet
WATER RESISTANCE	200m
BATTERY LIFE	10 Years
LUG TO LUG (TOP TO BOTTOM)	51.7mm

Setting the time and date

Pos. I Position of rest (watch running)

Pos. II Quick-change correction for date

Blocking time for the quick-change day correction is from approx. 9.30 pm and midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

Pos. III Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.



Strap fitting/options

The Hawk models can be fitted with a polymer strap, one-piece 24mm webbing or a stainless-steel bracelet.

With a 24mm lug width and 24mm spring bar fixing, straps are easily interchangeable using a forked spring bar tool. Many 24mm aftermarket straps are also compatible*

The Hawk straps exclusively available through nitewatches.com can be found [here](#).

The stainless-steel bracelet can be adjusted in length by adding or removing links and by also using the 3-micro adjustment on the buckle part of the strap.

**Nite Watches accept no responsibility with the sizing and fitting of any aftermarket straps.*

If you have any questions about the Hawk series then please email us on theteam@nitewatches.com.